


LCD COLOUR MONITOR

Model No. LSD7725

7.0" TFT LCD HD-SDI Colour Video Monitor, SDI and Composite video inputs/output. LED backlight, Metal Cased. PAL & NTSC, 4:3 aspect Ratio. Stand, VESA & "C" mountings.



Main Features:

- Resolution: 480000 pixels – 800xRGBx600
- LED Backlight, Low Current.
- Picture Ratio: 16:9 and 4:3.
- Brightness: 450 cd/m2
- Contrast Ratio: 400:1
- SDI and Composite Video input.
- Mounting: VESA 75, Stand, "C" mount.
- Metal Cabinet finished in Black.
- Full OSD with HOT keys.
- Tally indicator lights.
- Image Rotation. L/R/U/D.

The LSD7725 HD-SDI monitor with TFT active matrix technology, offers a sharp and high contrast display with universal application opportunities. LED backlight for low power. Metal cased for ruggedness with Sun Visor. Mounting via Stand, VESA 75mm and "C" mount. Easy to setup and adjust with Front panel HOT keys and OSD. Video image rotation and Video1/2 selection. Tally Indicator. An audio input enables sound output via headphones, Line out and Speaker. Ideal for Studio applications, Vehicle systems and High quality Video applications.

SPECIFICATIONS:

- Active area: 152.4 x 91.44 (WxH)mm. • Dot pitch: 0.063 x 0.19 (WxH)mm. • 262K Colours.
- PAL and NTSC Auto. • Data/Bit rate: 1.5Gbits. • Audio In/Out and via speaker.
- Response Time: 15/35 ms (Tr/Tf). • Viewing angle: Left/Right: 60°, Up/Down 40°.
- SDI Format: PAL/NTSC: 480i, 525i, 525/29.97, 1080i60. PAL: 625i, 625/25, 720P50, 720P59.94, 720P60, 1080i29, 1080i30, 1080i50, 1080i5994. PAL H:15.625, V:50Hz, C:4.43 & NTSC. H:15.75Khz, V:60Hz, C:3.58MHz.
- Controls: Menu, +, -, Up/Down image reverse L/R/U/D, Video 1/2, On/Off, On LED.
- Power Source: 12~24V DC, 480/280 mA, 5.76 Watts approx.
- Dimensions: Unit: 193 x 145 x 42. With stand: 240x164x60 Carton: 287 x 75 x 230 (WxHxD)mm.
- Weight: Unit: 1.1 Kgms, Carton: 2.18 Kgms. • Temp: Operation: -10°C~60°C, Storage: -20~70°.

Connections: Input: SDI: BNC, Composite Video 1/2: Phono Socket, Audio: Phono Socket. Output: SDI: 2 x BNC, Composite Video: Phono Socket, Audio: 3.5mm Jack socket. Tally: 15 pin Sub-D socket.

Standard accessories: AC adaptor, Stand, Hood Visor.

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO

Product Shop International Ltd

PO Box 5503, Newbury, Berkshire, RG14 6YP. UK

e-mail: sales@productshop.co.uk Website www.productshop.co.uk

Tel: +44 (0) 844 800 4433 Fax: +44 (0) 844 800 9876

Registered office: As above. Registered No. 3852764 VAT No. GB 727 0478 29