

# LCD COLOUR MONITOR

## Model No. 740VG

7.0" TFT LCD Colour Monitor VGA & Composite Video inputs. PAL & NTSC auto. Wide screen format 16:9 and 4:3 Ratio. Touch screen available 740VGT.



### Main Features:

- Resolution: 307200 pixels - 640 x 480
- Picture Ratio: 16:9 and 4:3
- Brightness: 250 cd/m<sup>2</sup>
- Contrast Ratio: 150:1
- Composite Video and PC input.
  
- Cabinet finished in Black.
- Mounting: Desk, Wall, Tray.
- Speaker 1 Watt 8 Ohms.
- Full OSD.

The 740VG with 7.0" TFT active matrix technology offers a High Brightness Sharp picture. Universal opportunities with VGA input for Computer, and Composite Video input for Camera & Video playback. Applications are endless including CCTV, In-Vehicle, Industrial and added flexibility with Touch Screen (model 740VGT). Attractively finished with Stylish black cabinet. Mini Din plugs for easy connection. Infra-red remote control.

### SPECIFICATIONS:

- Active area: 154.08 x 86.58 (WxH)mm. • PAL and NTSC Auto.
- Response Time: 18 ms (Tr/Tf). • Viewing angle: Left/Right: 45°, Up: 10° Down 25°.
- Controls: Down, Up, Input, Select, Menu, Power.
- Menu: Brightness, Contrast, Colour, Hue, Audio I/R (Not used), Reset, Expand, Exit.
- Remote Functions: Power On/Off, Menu, Video Select.
- Power Source: 12V DC, 700mA, 10 Watts approx. In-Line fuse: 5 Amps.
- Dimensions: Unit: 176 x 135 x 28. Tray: 202 x 160 x 28. Tray cut out: 186 x 144 x 20. Carton: 335 x 60 x 220 (WxHxD)mm.
- Weight: Unit: 0.47 Kgms, Carton: 1.44 Kgms. • Temp: Operation: -20°C~75°C, Storage: -30~85°.

**Connections:** Input: PC 15 pin D-sub socket, Video/Power 8 pin Mini Din socket. To 8 pin Mini Din plug Video 1 & 2, Phono sockets, DC open end wires.

**Standard accessories:** Power A/V Cable, VGA Cable, Stand, I/R Remote Control, Stand. Recessed Tray.

**Optional:** AC Adaptor.

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO