

# LCD COLOUR MONITOR

## Model No. AN035K

3.5" TFT LCD Colour Pal & NTSC Slim Line Monitor with Wrist Holder Bag & Composite Video V1 & V2 inputs. Left/Right image reverse.



The AN035K with TFT active matrix technology Slim Line model with low power consumption, offering a sharp and high brightness display with wide viewing angles. Features Composite Video V1 & V2 inputs. The AN035K has universal application potential with Video Systems of PAL & NTSC auto switching and is ideal for Surveillance Systems, Multimedia Video applications and Reverse Monitoring. Simple Mini din connection with sprung connector for secure connection to Video & Power.

### SPECIFICATIONS:

- Resolution: 112,320 pixels 480x234, Active Area: 72.0 x 50.54 (HxW)mm
- Video system PAL & NTSC Auto. Video 1 & Video 2 inputs.
- Brightness: 250 cd/m<sup>2</sup>, Contrast Ratio: 350:1
- Aspect Ratio: 4:3
- Viewing angle: 15° Up, 35° Down, 50° Left/Right
- Front Controls: V1 & V1, Brightness Up/Down, Image reverse, Power On/Off.
- Power Source: 12V DC, 300mA, 3.6 Watts approx.
- Dimensions:- Unit: 88 x 82 x 22mm WxHxD. Bag: 130x105x50mm (WxHxD).  
Carton: 245x75x175mm(WxHxD)
- Temp: Operation: -20°C ~ +70°C.
- Finished in Dark Grey. Weight:- Unit: 0.24kgms. Carton: 0.80kgms
- Connections: Input/Output: Flylead to 4 pin Mini Din socket.  
Mini Din Plug to: Video Input 1 & 2 Phono plugs, Power 2.1mm socket.
- All information correct at time of going to press
- Design and specification are subject to change without prior notice. E&OE.

### Standard Accessories

Mini Din Lead  
Unit Bag  
Wrist strap  
Carry Straps  
Battery + Charger  
Phono Video Lead