

LCD COLOUR MONITOR

Model No. AN501

5.0" TFT LCD Colour PAL & NTSC Monitor, New Panel, Slim Line with Stand for Desk or Wall mounting, Tray for Recessed, Headrest and Wall mounting. 11–30 Volts operation. E13 Certificate.



Main Features:

- Resolution: 224,640 pixels - 960 x 234
- Picture Ratio: 4:3
- Brightness: 400 cd/m2
- Contrast Ratio: 120:1
- Easy connect Mini Din lead.

- Mounting: Recessed Tray, Stand, "C" mount
- Audio via Speakers and Headphone socket.
- Cabinet finished in Grey and Black.
- Full OSD and Hot keys.
- Left/Right/Up/Down image reverse.
- Inputs: 2 x Composite, Audio.

The AN501 has TFT active matrix technology with low power consumption which offers a sharp and high brightness display with wide viewing angles. Features A/V 1 & 2 with Stereo Audio inputs. The AN501 has universal application potential with Video Systems of PAL & NTSC and is ideal for Surveillance Systems, Multimedia Video applications, Reverse Monitoring and Headrest Vehicle Systems with recessed Mounting Tray. Has rear sliding bracket for wall mounting with the Stand or can be recessed into the wall using the Tray.

SPECIFICATIONS:

- Active area: 101.8 x 74.4 (WxH)mm.
- PAL and NTSC Auto.
- Response Time: 10/10ms (Tr/Tf).
- Viewing angle: Left/Right: 60°, Up:40°, Down:60°.
- Controls: Menu, Up, Down, Minus, Plus, Channel V1/V2, Power.
- Power Source: 12V DC, 500mAmp, 5 Watts approx.
- Dimensions: Unit: 135 x 110 x 27. With Tray:167 x 140 x 34 Carton: 180 x 90 x170 (WxHxD)mm
- Weight: Unit: 0.35Kgms, Carton: 0.9Kgms.
- Temp: Operation: -10 ~ 65°C, Storage: -20 ~ 70°C.

Connections: Flylead to 10 pin Mini Din socket. Lead: 10 pin Mini Din Plug to: Stereo Audio & Video 1 and 2 Phono plugs and Power 2.1mm socket.

Standard accessories: Stand, Mini Din Lead, Recessed Tray, Tray removal tool.

Optional: AC adapter.

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO