

LCD COLOUR MONITOR

Model No. AN5601

5.6" TFT LCD Colour Monitor, NEW Panel, PAL & NTSC, 2 video inputs, 11-30 Volts, Wall mountable. Easy to use front controls, Image reverse and Speaker. E13 Certificate.



Main Features:

- Resolution: 224,640 pixels - 960 x 234
- Picture Ratio: 4:3
- Brightness: 250 cd/m2
- Contrast Ratio: 150:1
- Easy connect Mini Din lead.
- Mounting: Stand, "C" mount.
- Audio via Speakers and Headphone socket.

- Cabinet finished in Grey and Black.
- Full OSD and Hot keys.
- Left/Right/Up/Down image reverse.
- Inputs: 2 x Composite, Audio.

The AN5601 with NEW Panel TFT active matrix technology, Slim Line model with On-Screen Display, offering a sharp and high contrast display with wide viewing angle. Easy to use front controls. Audio via Speaker and Front Headphone socket. 2 video inputs and Quick connection via Mini din lead. It has universal application potential and is ideal for Surveillance Systems, Reverse Monitoring Vehicle Systems and Multimedia Video applications. Rear sliding bracket for wall mounting. Optional Tray for recessed mounting.

SPECIFICATIONS:

- Active area: 154.08 x 84.708 (WxH)mm. • PAL and NTSC Auto.
- Response Time: 10/10ms (Tr/Tf). • Viewing angle: Left/Right: 45°, Up:100°, Down:30°.
- Controls: Power, Vol+, Vol-, Image reverse, Contrast, Brightness, Colour, V 1 & 2.
- Power Source: 12V DC, 750 mA, 9 Watts approx.
- Dimensions: Unit: 148 x 124 x 35. Carton: 180 x 90 x 170 (WxHxD)mm
- Weight: Unit: 0.55Kgms, Carton: 0.875Kgms. • Temp: Operation: -10~65°C, Storage: -20~ 85°C.

Connections: Flylead to 10 pin Mini Din socket. Lead: 10 pin Mini Din Plug to: A/V 1 & 2 Phono plugs, Stereo Audio Phono Plugs, DC 2.1mm Socket. Headphone: 3.5mm Front socket.

Standard accessories: Stand and, 10 pin Mini Din Lead.

Optional: AC adapter, Tray and removal tool.

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO