


# LCD COLOUR MONITOR

## Model No. LCD104AK

10.4" TFT LCD Colour Video Monitor with XGA, 2 x Composite & Y/C (S-Video) BNC connectors and Video Loop through. Audio In/Out and via speakers. I/R Remote control. Optional: Touch screen and 19" Rack mounting. Other sizes available.



### Main Features:

- Resolution: 1024 x 768 - XGA
- Picture Ratio: 4:3
- Brightness: 400 cd/m<sup>2</sup>
- Contrast Ratio: 500:1
- Inputs: Composite, PC, S-Video.
- Mounting: VESA 75/100, Key Hole, Stand.
- Aluminum cabinet finished in Grey.
- Speaker: 2 Watts max.
- **Note: The image of the 19" rack mounting is showing a similar model.**

The LCD104AK with TFT technology, offers Professional sharp images and with high contrast ratio 500:1 and Brightness 400 cd/m<sup>2</sup> gives superb pictures. With BNC Connectors, Video Loop through, Audio In/Out connectors and Audio via speakers making it a truly versatile Monitor. Mounting options offering VESA 75 + 100 & Key hole mounting and with a Desk stand. Infra-Red remote control. All mounted in a Smart tough Aluminum Metal housing. This compact unit is ideal for Multimedia Video and Surveillance systems applications.

### SPECIFICATIONS:

- Active area: 211.2 x 158.4 (WxH)mm. • 16.7M Colours. • PAL and NTSC Auto.
- Response Time: 10/25ms (Tr/Tf). • Viewing angle: Left/Right: 89°, Up/ Down 89°.
- Controls/Indicators: Source, Menu, Item, Up, Down, Power. Front: On LED and I/R sensor.
- Power Source: 12V DC, 1.1 Amp, 13.2 Watts approx. AC Adaptor: 100-240V 50/60Hz 1.5Amps.
- Dimensions: 266 x 231 x 41 (55 with stand). Carton: 335 x 290 x 110 (WxHxD)mm.
- Weight: Unit: 2.08 Kgms, Carton: 3.10 Kgms. • Temp:Operation: -10~50°C, Storage: -20~ 60° C.

**Connections:** PC 15 pin Sub-D, Audio Out 3.5mm Jack socket, DC input: 2.1mm socket. Video In/Out 1 & 2: BNC, Y/C (S-Video) In: 4 pin mini din socket, Audio In/Out 1 & 2: Phono sockets.

**Standard accessories:** AC adapter, AC Mains Lead, I/R Remote Control.

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO