


LCD COLOUR MONITOR

Model No. LCD151AVS

15.0" TFT LCD Colour Monitor, XGA 1024 x 768, inputs of HDMI, PC, 2 x Composite, Y/C (S-Video), with 3D De-Interlace, BNC connectors and Video Loop through. Audio In, Out via Speakers, I/R Remote Control. Options: Touch screen. Other sizes available.



Main Features:

- Resolution: 1024 x 768 - XGA
- Picture Ratio: 4:3
- Brightness: 300 cd/m2
- Contrast Ratio: 700:1
- Inputs: HDMI, Composite, PC, S-Video.
- Mounting: VESA 75/100, Key Hole, Stand.
- PIP/POP Function PC & Video.
- Plastic front cabinet finished in Grey.
- 3D De-Interlaced Technology.
- Anti-blur/image auto.
- Speaker 2 x 2 Watts max.

The LCD151AVS with TFT technology, offers Professional sharp images and with high contrast ratio gives superb pictures. With BNC Connectors, Video Loop through, Audio In/Out via speakers this is a truly versatile Monitor. Various mounting options and all finished in a Smart tough Plastic front and Metal rear housing. This compact unit is ideal for Multimedia Video and Surveillance systems applications.

SPECIFICATIONS:

- Active area: 304 x 228 (WxH)mm.
- 16.2M Colours.
- PAL and NTSC Auto.
- Response Time: 6.0/19ms (Tr/Tf).
- Viewing angle: Left/Right: 75°, Up: 60°, Down: 55°.
- Controls/Indicators: Front: On LED, I/R sensor. Rear: Source, Menu, Item, Up, Down, Power.
- Power Source: 12V DC, 2.16 Amp, 26 Watts approx. AC Adaptor: 90-260V 50/60Hz 5Amps.
- Dimensions: 357 x 283 x 64 (80 with stand). Carton: 470 x 420 x 170 (WxHxD)mm.
- Weight: Unit: 3.2 Kgms, Carton: 4.46 Kgms.
- Temp: Operation: 0°C~50°C, Storage: -10~ 60°.

Connections: HDMI Socket. PC 15 pin Sub-D, Y/C (S-Video): 4 pin mini din socket, Video In/Out 1 and 2: BNC, Audio In: Right and Left Phono sockets. PC Audio in: 3.5mm Jack socket, DC input: 2.1mm socket. AC adaptor: IEC socket.

Standard accessories: AC adapter, AC Mains Lead, I/R Remote Control.

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO