

LCD COLOUR MONITOR

Model No. LCD154AV

15.4" TFT LCD Colour Video Wide Screen Monitor, DVI, PC WXGA, Composite Video, Y/C (S-Video), De-Interlace, BNC connectors and Video Loop through. Audio In/Out and via speakers. I/R Remote Control. Options: RS232 control, Touch Screen, and 19" Rack mount. Other Wide Screen models 22.0", 26.0", 32.0" and 42.0".



The LCD154AV with TFT technology and De-Interlacing offers Professional sharp images and with high contrast ratio 800:1 and Brightness 600 cd/m² gives superb pictures. With DVI interface and BNC Connectors, Video Loop through, Audio In/Out connectors and Audio via speakers makes it truly versatile Monitor. Mounting options offering VESA 75 + 100 & Key hole mounting and with Desk stand. All mounted in a Smart tough Aluminium, Metal housing. This compact unit is ideal for Multimedia Video and Surveillance systems applications.

SPECIFICATIONS:

- High resolution 1,024,000 pixels, 1280x800 Active area: 329 x 204 (WxH)mm
 - PAL & NTSC Auto. Brightness 600 cd/m², Contrast Ratio: 800:1. 16.2M Colours.
 - Picture Ratio: 16:9 & 4:3. Response Time: 5ms (Tr + tf).
 - Controls: Source, Menu, Item, Up, Down, Power.
 - Viewing angle: Left/Right/Up/Down:60/60/40/60°.
 - Power Source: 12V DC, 1.5 Amp, 17.5 Watts approx.
 - Dimensions: Unit: 385 x 258 x 63. Carton: 466 x 385 x 160 (WxHxD)mm.
 - Temp: Operation: -0°C ~ +50°C. Storage: -20°C ~ +60°C
 - Finished in Dark Grey. Weight: Unit: 2.88 Kgms, Carton: 7.73 Kgms
- Connections: DVI socket, PC 15 pin Sub-D, Audio Out 3.5mm Jack socket, DC input: 2.1mm socket. Video In/Out 1 & 2: BNC, Y/C (S-Video) Input: 4 pin mini din socket, Audio In/Out 1 & 2: Phono sockets.

Standard Accessories
AC adapter & Lead
I/R Remote Control

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO