LCD COLOUR MODULE
Model No. LCD156mod

15.6” TFT LCD Colour Module, WXGA 1366 x 768, inputs of HDMI, PC, 2 x Composite, Y/C (S-Video), with 3D De-Interlace, BNC connectors and Video Loop through. Audio In, Out, I/R Remote sensor. Options: Touch screen. Other sizes available.

Main Features:

- Resolution: 1366 x 768 - WXGA
- Picture Ratio: 16:9 and 4:3
- Brightness: 300 cd/m2
- Contrast Ratio: 500:1
- Inputs: HDMI, Composite, PC, S-Video.

- Mounting: Panel, PCB and Inverter.
- PIP/POP Function PC & Video
- 3D De-Interlaced Technology.
- Anti-blur/image auto.

The LCD156mod with TFT technology offers Professional sharp images and with high contrast ratio gives superb pictures. With BNC Connectors, Video Loop through, Audio In/Out this is a truly versatile Module. This compact unit is ideal for Multimedia Video and Surveillance systems applications.

SPECIFICATIONS:

- Active area: 334.2 x 193.5 (WxH)mm. • 16.7M Colours. • PAL and NTSC Auto.
- Response Time: 6/2 ms (Tr / Tf). • Viewing angle: Left/Right: 85°, Up/ Down 80°.
- Controls/Indicators: On LED, I/R sensor. Source, Menu, Item, Up, Down, Power.
- Power Source: 12V DC, 1.5 Amp, 19 Watts approx.
- Dimensions: LCD Panel: 363.8 x 215.9 x 14.3. Main PCB: 160 x 98 x 10. (WxHxD) mm
- Weight: Unit: 2.5 Kgms. • Temp:Operation: 0°C~40°C, Storage: -20~60° C.

Connections: HDMI Socket. PC 15 pin Sub-D, Y/C (S-Video): 4 pin mini din socket, Video In/Out 1 and 2: BNC, Audio In: Right and Left Phono sockets. PC Audio in: 3.5mm Jack socket, DC input: 2.1mm socket.
Standard accessories: None.

- *Please note: A degree of technical knowledge will be required to install this module.*

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO