

# LCD COLOUR MONITOR

## Model No. LCD170AV

17.0" TFT LCD Colour Video Monitor with SXGA, De-Interlaced, DVI, 2 x Composite & Y/C (S-Video) BNC connectors and Video Loop through. Audio In/Out and via speakers. Optional: RS232 control, Touch screen and 19" Rack mounting. Other models 10.4", 12.1", 15.0", 20.0", 22.0", 26.0", 32.0 and 42.0".



The LCD170AV with TFT technology, offers Professional sharp images and with high contrast ratio 500:1 and Brightness 400 cd/m<sup>2</sup> gives superb pictures. With DVI interface and BNC Connectors, Video Loop through, Audio In/Out connectors and Audio via speakers is a truly versatile Monitor. Mounting options offering VESA 75 + 100 & Key hole mounting and with Desk stand. All mounted in a Smart tough Aluminium Metal housing. This compact unit is ideal for Multimedia Video and Surveillance systems applications.

### SPECIFICATIONS:

- High resolution 1,310,720 pixels 1280x1024 Active area: 337.92 x 270.33 (WxH)mm
- PAL & NTSC, Brightness 400 cd/m<sup>2</sup>, Contrast Ratio: 500:1. 16.2M Colours.
- Response Time: 8ms (Tr + tf). Picture Ratio: 4:3
- Controls: Source, Menu, Item, Up, Down, On LED, Power.
- Viewing angle: Left/Right 70° Up/Down 70°.
- Power Source: 12V DC, 2 Amp, 38 Watts approx.
- Dimensions:- Unit: 420x352x80 (WxHxD)mm. Carton: 640x510x180mm
- Temp: Operation: -10°C - 60°C
- Finished in Silvery Bronze. Weight: Unit: 5.57 kgms, Carton: 7.52 kgms
- Connections: DVI socket, PC 15 pin Sub-D, Audio Out 3.5mm Jack socket, DC input: 2.1mm socket. Video In/Out 1 & 2: BNC, Y/C (S-Video) In/Out: 4 pin mini din socket, Audio In/Out 1 & 2: Phono sockets.

<b>Standard Accessories</b> AC adapter AC Mains Lead I/R Remote Control
--

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO