

CCTV LCD Monitor with DVR

Model No. LCD171H4

17.0" TFT LCD Colour SXGA Video Security Monitor, 4 Channel Multiplexer with DVR, includes a 500Gb disk drive. H.264 video compression. Audio In/Out. Digital Zoom. Password control.



The LCD171H4 is an amazing compact unit, 17" TFT LCD Monitor with internal 4 channel Multiplexer with DVR. With Alarm function. This compact unit is ideal for CCTV Multimedia Video and Surveillance systems applications. This unit is Ideal for shops or small units. Can be networked to make larger systems. The unit is supplied with a 500Gb SATA Hard Disc Drive. Infra-Red control. Real Triplex with Recording, Live time and Playback at the same time.

SPECIFICATIONS:

Monitor:

- High resolution 1310720 pixels 1280x1024.
- Active area: 337.92 x 270.33 (WxH) mm.
- PAL & NTSC Auto. Viewing angle: L/R/U/D: 85/85/85/75°.
- Brightness 300 cd/m², Contrast Ratio: 500:1. Picture Ratio: 4:3
- Front I/R sensor and On LED. Side/rear controls: Menu, Down, Up, On/Off.

VIDEO Function:

- Video input: Camera x 4. Format: PAL or NTSC auto. Daylight Saving time.
- Network: Ethernet Compression H.264. Support: PPPoE/Static/DHCP IP, DDNS. FTP, E-mail. Multi-remote client x 4. PDA Phone Support (MPEG4). CMS: 3GPP (MPEG4).
- Recording Rate: CIF:100 FPS 360x288 . Half D1: 720x288, 50 PS. Compression rate: 1-6Kbytes

Standard Accessories

AC adapter + Lead
PS2 Mouse, User CD
I/R Remote Control
A/V Lead Phono
3.5mm to Phono Lead
BNC to Phono plug

All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO.

Model No. LCD171H4 Continued.

- Display Image: Full screen or Quad 4 split. Monitor Output.
- Playback: Search: Percent, Time/Date, Event. Speed: Forward & Backwards: 2X, 4X, 8X.
- Alarm: I/P: 4 x NO/NC, O/P: 1 x NO/NC. Motion detection 30x24 grids, Video Loss, Buzzer.
- Remote: Web Viewer: Live, Playback, Backup, Setting.
- User interface: RS485 PTZ camera control, USB mouse.

- Power Source: 12V DC, 3.0 Amp, 40 Watts approx.
- Dimensions:-Unit: 390 x 325 x 75. with Stand:390x375x193. Carton:545x485x173 (WxHxD)mm.
- Finished in Black. Weight:- Unit: 4.92 kgms. Carton: 5.5 kgms.

Connections:

DC Input: 2.1 mm DC Socket. Video/Camera input: 4 x BNC. Monitor out: BNC.

Mouse/PS2: USB. USB: B type. Ethernet: RJ-45. Audio In/Out: Phono.

12 pin Push connector. RS485: T+, T-, R+, R-, Alarm: 1-4+Ground, Relay: NC + Com + NO.

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO.