


LCD COLOUR MONITOR

Model No. LCD191AVS

19.0" TFT LCD Colour Monitor, LED Back Light, inputs of HDMI, PC, 2 x Composite, Y/C (S-Video), with 3D De-Interlace, BNC connectors and Video Loop through. Audio In, Out via Speakers, I/R Remote Control. Options: Touch screen. Other sizes available.



Main Features:

- Resolution: 1280 x 1024 - SXGA
- Picture Ratio: 4:3
- Brightness: 250 cd/m², LED Backlight.
- Contrast Ratio: 1000:1
- Inputs: HDMI, Composite, PC, S-Video.
- Mounting: VESA 75/100, Key Hole, Stand.
- PIP/POP Function PC & Video
- Plastic front cabinet finished in Grey.
- 3D De-Interlaced Technology.
- Anti-blur/image auto.
- Speaker 2 x 2 Watts max.

The LCD191AVS with TFT technology, offers Professional sharp images with LED Backlight and high contrast ratio gives superb pictures. With BNC Connectors, Video Loop through, Audio In/Out via speakers this is a truly versatile Monitor. Various mounting options and all finished in a Smart tough Plastic Front and metal rear housing. This compact unit is ideal for Multimedia Video and Surveillance systems applications.

SPECIFICATIONS:

- Active area: 376.3 x 301 (WxH)mm. • 16.7M Colours. • PAL and NTSC Auto.
- Response Time: 1.3/3.7 ms (Tr / Tf). • Viewing angle: Left/Right: 85°, Up/ Down 85°.
- Controls/Indicators: Source, Menu, Item, Up, Down, On LED, Power, I/R sensor.
- Power Source: 12V DC, 2.0 Amp, 24 Watts approx. AC Adaptor: 90~260V 50/60Hz 5Amps.
- Dimensions: 425 x 357 x 52 (66.78 with stand). Carton: 550 x 500 x 170 (WxHxD)mm.
- Weight: Unit: 4.78 Kgms, Carton: 6.72 Kgms. • Temp: Operation: 0°C~50°C, Storage: -10~ 60°.

Connections: HDMI Socket. PC 15 pin Sub-D, Y/C (S-Video): 4 pin mini din socket, Video In/Out 1 and 2: BNC, Audio In: Right and Left Phono sockets. PC Audio in: 3.5mm Jack socket, DC input: 2.1mm socket. AC adaptor: IEC socket.

Standard accessories: AC adapter, AC Mains Lead, I/R Remote Control.

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO