

LCD COLOUR MONITOR

Model No. LCD200AV

20.0" TFT LCD Colour Video Monitor with SVGA, De-Interlaced, DVI, 2 x Composite & Y/C (S-Video) BNC connectors and Video Loop through. Audio In/Out and via speakers. Optional: RS232 control, Touch screen and 19" Rack mounting. Other models 10.4", 12.1", 15.0", 15.4", 17.0" 22.0", 26.0", 32.0" and 42.0".



The LCD200AV with TFT technology, offers Professional sharp images and with high contrast ratio 500:1 and Brightness 450 cd/m² gives superb pictures. With DVI interface and BNC Connectors, Video Loop through, Audio In/Out connectors and Audio via speakers is a truly versatile Monitor. Mounting options offering VESA 75 + 100 & Key hole mounting and with Desk stand. All mounted in a Smart tough Aluminium Metal housing. This compact unit is ideal for Multimedia Video and Surveillance systems applications.

SPECIFICATIONS:

- High resolution 480,000 pixels 800x600 Active area: 480 x 306 (WxH) mm.
 - PAL & NTSC & SECAM Auto. 16.7M Colours.
 - Brightness 450 cd/m², Contrast Ratio: 500:1. Picture Ratio: 4:3
 - Dot pitch: 0.51x 0.51. Response Time: 16ms (Tr + tf).
 - Controls: Source, Menu, Item, Up, Down, On LED, Power.
 - Viewing angle: Left/Right 80° Up/Down 60°.
 - Mounting: VESA 75/100, Keyhole, Removable Desk Stand.
 - Power Source: 12V DC, 4.5 Amp, 55 Watts approx.
 - Temp: Operation: -10°C - 60°C
 - Dimensions:-Unit: 490.5x388.5x81 (WxHxD)mm. Carton: 600x610x170 (WxHxD)mm.
 - Finished in Silvery Bronze. Weight:- Unit: 7.10 kgms. Carton: 9.22 kgms
- Connections: DVI socket, PC 15 pin Sub-D, Audio Out 3.5mm Jack socket, DC input: 2.1mm socket. Video In/Out 1 & 2: BNC, Y/C (S-Video) In/Out: 4 pin mini din socket, Audio In/Out 1 & 2: Phono sockets.

Standard Accessories

AC adapter
AC Mains Lead
I/R Remote Control

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO