

LCD COLOUR MONITOR

Model No. LCD220AV

22.0" TFT LCD Colour Video Wide Screen Monitor, De-Interlace, inputs of DVI, Composite & Y/C (S-Video) BNC connectors and Video Loop through. Audio In/Out and via speakers. I/R Remote Control. Options: RS232 control, Touch screen. Other models 10.4", 12.1", 15.0", 15.4", 17.0", 19.0", 20.0", 26.0", 32" and 42.0".



The LCD220AV with TFT technology and De-Interlaced picture offers Professional sharp images and with high contrast ratio 1000:1 and Brightness 300 cd/m² gives superb pictures. With DVI interface and BNC Connectors, Video Loop through, Audio In/Out connectors and Audio via speakers makes it truly versatile Monitor. Mounting options offering VESA 75 + 100 & Key hole mounting and with Desk stand. All mounted in a Smart tough Aluminium, Metal housing. This compact unit is ideal for Multimedia Video and Surveillance systems applications.

SPECIFICATIONS:

- High resolution 1,764,000 pixels, 1680x1050 Active area: 473.76 x 296.0 (WxH)mm
 - PAL & NTSC Auto. Brightness 300 cd/m², Contrast Ratio: 1000:1.
 - Picture Ratio: 16:9 & 4:3. Response Time: 5 ms (Tr + tf). 16.7M Colours.
 - Controls: Source, Menu, Item, Up, Down, Power.
 - Viewing angle: Left/Right/Up/Down 80/80/85/85°.
 - Power Source: 12V DC, 3.3 Amp, 40 Watts approx.
 - Dimensions: Unit: 525 x 347 x 70. Carton: 617 x 500 x 180 (WxHxD)mm.
 - Temp: Operation: -0°C ~ +50°C. Storage: -20°C ~ +60°C
 - Finished in Dark Grey. Weight: Unit: 6.12 Kgms, Carton: 8.28 Kgms
- Connections: DVI socket, PC 15 pin Sub-D, Audio Out 3.5mm Jack socket, DC input: 2.1mm socket. Video In/Out 1 & 2: BNC, Y/C (S-Video) In: 4 pin mini din socket, Audio In/Out 1 & 2: Phono sockets.

Standard Accessories
AC adapter + Lead
I/R Remote Control

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO