

LCD COLOUR MONITOR

Model No. LCD236HDmod

23.6" TFT LCD **Full High Definition** Colour Wide Screen Module, LED Back Light, 1920 x 1080, inputs of HDMI, PC WUXGA, 2 x Composite, Y/C (S-Video), with 3D De-Interlace, BNC connectors and Video Loop through. Audio In, Out, I/R Remote connection. Other sizes available.



Main Features:

- Resolution: 1920 x 1080P - WUXGA
- LED Back Light
- Picture Ratio: 16:9
- Brightness: 300 cd/m2 LED Back light.
- Contrast Ratio: 1000:1

- PIP/POP Function PC & Video
- Mounting: Panel, PCB and Inverter.
- 3D De-Interlaced Technology.
- Anti-blur/image auto.

The LCD236HDmod with Full HD TFT technology, offers Professional sharp images and with high contrast ratio gives superb pictures. With HDMI and BNC Connectors, Video Loop through, Audio In/Out this is a truly versatile Monitor. This compact unit is ideal for Multimedia Video and Surveillance systems applications.

SPECIFICATIONS:

- Active area: 521.28 x 293.22 (WxH)mm. • 16.7M Colours. • PAL and NTSC Auto.
- Response Time: 1.5/3.5 ms (Tr/Tf). • Viewing angle: Left/Right: 85°, Up/ Down 80°.
- Controls/Indicators: Front: On LED, I/R sensor. Rear: Source, Menu, Item, Up, Down, Power.
- Power Source: 12V DC, 3.16 Amp, 38 Watts approx.
- Dimensions: Panel: 544.8 x 320.5 x 11.4. Main PCB: 160 x 98 x 10. (WxHxD)mm.
- Weight: Unit: 2.45Kgms. • Temp: Operation: 0°C~50°C, Storage: -20~ 60°.

Connections: HDMI Socket. PC 15 pin Sub-D, Y/C (S-Video): 4 pin mini din socket, Video In/Out 1 and 2: BNC, Audio In: Right and Left Phono sockets. PC Audio in: 3.5mm Jack socket, DC input: 2.1mm socket.

Standard accessories: None.

• *Please note: A degree of technical knowledge will be required to install this module.*

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO