


LCD COLOUR MONITOR

Model No. LCD320HD

31.5" TFT LCD **Full High Definition** Colour Wide Screen Monitor, WUXGA 1920 x 1080P, inputs of HDMI, PC, 2 x Composite, Y/C (S-Video), with 3D De-Interlace, BNC connectors and Video Loop through. Audio In, Out via Speakers, I/R Remote Control. Other sizes available.



Main Features:

- Resolution: 1920 x 1080P - WUXGA
- Picture Ratio: 16:9
- Brightness: 450 cd/m2
- Contrast Ratio: 5000:1
- PIP/POP Function PC & Video
- Mounting: VESA 100/200, Key Hole, Stand.
- Aluminum cabinet.
- Finished in Grey.
- 3D De-Interlaced Technology.
- Anti-blur/image auto.
- Speaker 2 x 2 Watts max.

The LCD320HD with Full HD TFT technology, offers Professional sharp images and with high contrast ratio gives superb pictures. With BNC Connectors, Video Loop through, Audio In/Out via speakers this is a truly versatile Monitor. Various mounting options and all finished in a Smart tough Aluminium Metal housing. This compact unit is ideal for Multimedia Video and Surveillance systems applications.

SPECIFICATIONS:

- Active area: 698 x 392.85 (WxH)mm. • 16.7M Colours. • PAL and NTSC Auto.
- Response Time: 8 ms (G to G). • Viewing angle: Left/Right: 89°, Up/ Down 89°.
- Controls/Indicators: Source, Menu, Item, Up, Down, On LED, Power, I/R sensor.
- Power Source: 90 ~ 264 VAC, 80 Watts approx.
- Dimensions: 785.6 x 477.2 x 100 (115 with stand). Carton: 870 x 670 x 218 (WxHxD)mm.
- Weight: Unit: 12.52Kgms, Carton: 14.98Kgms. • Temp: Operation: 0°C~50°C, Storage: -20~ 60°.

Connections: HDMI Socket. PC 15 pin Sub-D, Y/C (S-Video): 4 pin mini din socket, Video In/Out 1 and 2: BNC, Audio In: Right and Left Phono sockets. PC Audio in: 3.5mm Jack socket, AC input: IEC socket

Standard accessories: AC Mains Lead, I/R Remote Control.

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO