

LCD COLOUR MONITOR


Model No. LM1950

19.0" TFT LCD Colour Video Monitor Mounted in a rugged IP65 Waterproof metal cabinet with SXGA, Composite & Y/C (S-Video) inputs. Front controls. Other sizes available.



Main Features:

- Resolution: 1280 x 1024 - SXGA
- Picture Ratio: 4:3
- Brightness: 450 cd/m2
- Contrast Ratio: 1000:1
- IP65 waterproof rating.



- Inputs: Composite, PC, S-Video.
- Mounting: Recessed, VESA 75 or Stand.
- Metal cabinet finished in Black.
- Front Controls.

The LM1950 with TFT technology, offers a sharp and high contrast ratio of 1000:1. The unit is mounted in a Waterproof IP65 rugged metal housing. Recessed Mounting, VESA 75mm with optional stand. SXGA, S-Video (Y/C) and Composite Video inputs. Easy to use front controls. The LM1950 is ideal for Surveillance systems and Multimedia Video applications in severe conditions. Optional Mounting bracket and Touch Screen.

SPECIFICATIONS:

- Active area: 376.6 x 301.0 (WxH)mm. • 16.2M Colours. • PAL and NTSC Auto.
- Response Time: 5ms (Tr/Tf). • Viewing angle: Left/Right: 75°, Up/Down: 70°.
- Front controls/Indicators: On/Off, Auto, Up, Power, Down/Input select, Menu, LED, Brightness.
- OSD Function: Auto Adjust. Colour Adjust: Brightness/Contrast/Hue/Saturation/Sharpness. Manager: Reset/Language.
- Power Source: 12V DC, 2.45 Amp, 29 Watts approx. AC Adaptor: 100-240V 50/60Hz 1.5Amps.
- Dimensions: 483 x 399 x 52. Carton: 560 x 240 x 550 (WxHxD)mm.
- Weight: Unit: 12 Kgms, Carton: 13.5 Kgms. • Temp: Operation: 0°C~50°C, Storage: -20~ 60°.

Connections: Power input: DC: 2.1mm, VGA: 15 pin Sub-D, S-Video input: 4 pin mini din, Video input: Phono Plug. AC adaptor: IEC socket.

Standard accessories: AC adapter, AC Mains Lead, VGA lead, Video lead, S-Video lead.

- All information correct at time of going to press. Design and specification are subject to change without prior notice. E&EO